

- Heavy duty shelving
- Shelving racks
- Cantilever racks



Brass Regalanlagen GmbH
 Im Sichert 14 + 16, 74613 Öhringen
 Phone: +49 (0) 7941 / 64 69 66-0
 Fax: +49 (0) 7941 / 64 69 66-20
 Email: info@brass-regalbau.de
www.brass-regalbau.de

SHELF LOAD

When loading the shelves, the maximum values specified by the manufacturer must be observed. Safe use can only be guaranteed within these limits.

- **This info panel** provides simplified, general values
- **Load capacity stickers on the shelf** (at the end of each row of shelves, on the inside of the stand) indicate the specific values for each shelf
- Comprehensive tables can be found in the **assembly and operating instructions** supplied with the respective shelving system

If you have any questions, please contact your safety officer or the manufacturer.

Heavy duty shelf system SL100 (70-mm plug-in grid)

max. bay load: 12,000 ¹ / 15,000 kg ²

Cross member type		bay width up to	max. shelf load
RT60	H 60 mm	2700 mm	600 kg
RT100	H 100 mm	2700 mm	2000 kg
RT120	H 120 mm	2700 mm	3000 kg
RTS120	H 120 mm, reinforced	2700 mm	3600 ¹ / 4200 kg ²

¹ for stands SL100/2, 2 mm plate thickness ² for stands SL100/3, 3 mm plate thickness

Wide span shelf LPR (40-mm plug-in grid)

max. bay load: 2500 kg (for shelf depths up to 750 mm)

Cross member type		bay width up to	max. shelf load
RP104	H 55 mm + 15 mm stop	2540 mm	540 kg
RP116	H 80 mm + 15 mm stop	2540 mm	1100 kg